

AMENDMENTS TO THE CLAIMS

1-27 (CANCELLED)

28. (Previously Presented) A miniature endoscope for orthopedic imaging comprising:
- a probe for orthopedic diagnostic imaging, the probe including a fiber optic imaging channel having a diameter in a range of 0.6 mm to 1.6 mm and the probe having a diameter less than 2 mm and a mounting hub;
 - a tube surrounding the imaging channel;
 - a fiber optic illumination channel within the probe that is concentric about the tube and the imaging channel and a light source that is optically coupled to the fiber optic illumination channel with the mounting hub attached to the handle, the illumination channel having a thickness in a range of 0.1 mm to 0.2 mm;
 - an outer tube around the fiber optic illumination channel;
 - a handle removably attached to the probe with a connector;
 - a cannula that receives a distal end of the probe such that the distal end of the probe slides within the cannula, the cannula having a locking mechanism at a proximal end that attaches to the probe;
 - a sterile barrier attached to the mounting hub that can be extended over the handle;
 - a first lens and a second lens that are optically coupled to a distal end of the imaging channel;
 - an optical relay mounted in the handle and optically coupled to a proximal end of the imaging channel; and
 - an imaging device mounted in the handle and optically coupled to a proximal end of the optical relay.
29. (Original) The miniature endoscope of Claim 28 wherein the imaging device comprises a charge coupled device.
30. (Original) The miniature endoscope of Claim 28 wherein the imaging channel comprises a transparent material having a refractive index of at least 1.6.

31. (Original) The miniature endoscope of Claim 30 wherein the imaging light channel comprises a glass rod.
32. (Original) The miniature endoscope of Claim 31 wherein the glass rod comprises an F2 or an F7 glass.
33. (Previously Presented) The miniature endoscope of Claim 28 further comprising a light absorbing layer around the imaging channel.
34. (CANCELLED)
35. (Previously Presented) The miniature endoscope of Claim 28 wherein the illumination channel is coupled to the light source with a fiber optic connector.
- 36-38 (Cancelled)
39. (Previously Presented) The miniature endoscope of Claim 28 wherein the endoscope has a display connected to the imaging device for arthroscopic examination.
- 40-80 (CANCELLED)
81. (Previously Presented) The endoscope of claim 1 further comprising a tube around the optical waveguide and an outer tube around the fiber optic illumination channel.
82. (Previously Presented) the endoscope of claim 81 wherein the outer tube is a plastic material.
- 83-84 (CANCELLED)
85. (Previously Presented) The endoscope of claim 84 further comprising an image processing sequence.
86. (Previously Presented) The endoscope of claim 85 wherein the image processing sequence subtracts a stored light distribution pattern from a video image.

87. (Previously Presented) The endoscope of claim 86 wherein the stored light distribution pattern corresponds with a light reflection pattern for the endoscope.

88. (Previously Presented) The endoscope of claim 81 wherein the tube comprises a metal.

89-90 (CANCELLED)

91. (New) A miniature endoscope for orthopedic imaging comprising:

- a probe for orthopedic diagnostic imaging, the probe including a fiber optic imaging waveguide that transmits an image, and having a diameter of less than 2 mm and a length between 2 cm and 10 cm, the probe having a mounting hub;

- a fiber optic illumination channel within the probe that is concentric about the optical waveguide, the illumination channel being positioned between an inner sheath and an outer sheath;

- a handle removeably attached to the mounting hub of the probe with a connector;

- a light source that is optically coupled to the fiber optic illumination channel with the mounting hub;

- a cannula that receives a distal end of the probe such that the outer sheath slides within the cannula, the cannula having a locking mechanism at a proximal end that attaches to the probe;

- a sterile barrier attached to the mounting hub and that can be extended over the handle;

- an optical lens coupled to a distal end of the waveguide;

- an optical relay mounted in the handle and that is optically coupled to a proximal end of the waveguide; and

- an imaging device mounted in the handle at a proximal end of the optical relay that receives an image from the optical waveguide.

92. (New) The miniature endoscope of Claim 91 wherein the endoscope has an outer diameter of 1.6 mm or less.

93. (New) The miniature endoscope of Claim 91 wherein the waveguide has an outer diameter between 0.6 and 1.6 mm.
94. (New) The miniature endoscope of Claim 91 wherein the illumination channel includes a binary phase ring which disperses light from the illumination channel.
95. (New) The miniature endoscope of Claim 91 wherein the waveguide comprises a glass having a refractive index in the range between 1.6 and 1.9.
96. (New) The miniature endoscope of Claim 91 wherein the waveguide comprises a glass rod.
97. (New) The miniature endoscope of Claim 91 wherein the optical waveguide further comprises a light absorbing layer having a thickness between 5 and 10 μ m.
98. (New) The miniature endoscope of Claim 91 wherein the optical waveguide further comprises a light absorbing layer having an extramural absorption glass.
99. (New) The miniature endoscope of Claim 91 wherein the optical waveguide further comprises a light absorbing layer having a refractive index of 1.6 or less.
100. (New) The miniature endoscope of Claim 91 wherein the illumination channel has a wall thickness in a range of 0.1 mm and 0.2 mm.
101. (New) The miniature endoscope of Claim 91 wherein the illumination channel has a refractive index in a range between 1.4 and 1.6.
102. (New) The miniature endoscope of Claim 91 wherein the outer sheath comprises a metal tube.
103. (New) The miniature endoscope of Claim 102 wherein the outer sheath comprises a polyamide coating.
104. (New) The miniature endoscope of Claim 103 wherein the polyamide coating has a thickness between 100 and 150 μ m.

105. (New) The miniature endoscope of Claim 91 wherein the optical relay comprises one or more lenses.
106. (New) The miniature endoscope of Claim 91 wherein the optical lens comprises a plastic lens.
107. (New) The miniature endoscope of Claim 91 wherein the imaging device comprises a charge coupled device.
108. (New) The miniature endoscope of Claim 91 wherein the cannula further comprises a distal needle that penetrates tissue.
109. (New) The miniature endoscope of Claim 91 further comprising a display connected to the imaging device.
110. (New) The miniature endoscope of Claim 91 wherein the illumination channel is optically coupled to a light source with a lens in the handle.
111. (New) The miniature endoscope of Claim 91 further comprising an optical coupler that optically connects the light source to the illumination channel.
112. (New) The miniature endoscope of Claim 91 wherein the cannula further comprises a fluid delivery port.
113. (New) The miniature endoscope of Claim 112 wherein the barrier is attached to a rigid waveguide housing that is connected to the handle.
114. (New) The miniature endoscope of Claim 91 wherein the light source comprises a lamp within the handle that is optically coupled to the illumination channel.
115. (New) The endoscope of claim 91 wherein the endoscope probe has a length to diameter ratio between 40:1 and 60:1.
116. (New) The endoscope of claim 91 further comprising a computer connected to the imaging

device.

117. (New) The endoscope of claim 1 wherein the concentric illumination channel has a thickness of 91 microns.
118. (New) The endoscope of claim 1 wherein the concentric illumination channel has a thickness of 91 microns.